

View Online at <https://aerobasegroup.com/nsn/5935-00-879-8615>

Thread Class:

2b and 2c

Thread Direction:

Right-hand and left-hand

Overall Length:

Between 2.865 inches and 2.885 inches

Overall Height:

1.173 inches

Overall Width:

Between 1.340 inches and 1.360 inches

Unthreaded Mounting Hole Diameter:

Between 0.133 inches and 0.165 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.807 inches and 0.817 inches

Distance Between Mounting Facility Centers:

Between 2.495 inches and 2.505 inches

Threaded Device Type:

Coupling facility and back shell

Mating End Quantity:

15

Polarization Method:

Polarization boss and jackscrew

Connector Locking Method:

Screw

Thread Size:

0.250 inches and 0.219 inches

Insert Material:

Plastic single mating end and glass single mating end

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end or mil-p-19833, type gdi-30f military specification single material response single mating end

Special Features:

Polarized at position x

Test Data Document:

81349-mil-c-28748/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf and unef and unef

Specification Data:

81349-mil-c-28748/09 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.