

View Online at <https://aerobasegroup.com/nsn/5935-00-880-2669>

Body Style:

Straight shape, internal coupling w/strain relief

Body Length:

2.047 inches

Overall Diameter:

1.305 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Cable Entrance Diameter:

0.500 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

16-8 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1000.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Connector Cable Strain Relief Method:

Cable clamp w/telescoping bushing and bushing

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 1, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, grade e federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Shell Material Specification:

Qq-a-591 federal specification single material response

Included Contact Quantity:

8 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.008 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

96906-ms3116 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.