Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-880-3253

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
1.250 inches
Overall Height:
0.530 inches
Overall Width:
0.270 inches
Environmental Protection:
Shock resistant and vibration resistant
Distance Between Mounting Facility Centers:
1.000 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
26 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Osteles well simple meeting and simple to the time

Solder well single mating end single contact grouping

NSN 5935-00-880-3253

Electrical Receptacle Connector - Page 2 of 2



	rial Specification:
	B, type gdi-30 military specification single material response single mating end
Included Co	ontact Quantity:
26 single ma	ating end single contact grouping
Included Co	ontact Type:
Round pin s	ingle mating end single contact grouping
Precious M	aterial And Location:
Contact surf	aces gold
Precious M	aterial And Weight:
0.026 gold g	rains, troy
Precious M	aterial:
Gold	
Thread Seri	ies Designator:
Unc	
Shelf Life:	
N/a	
Unit Of Mea	asure:
Demilitariza	ation:
No	
Fiig:	
A039b0	
Mil-std (mil	itary Standard):
Mil-m-19833	spec