
# NSN 5935-00-880-3929

Tip Jack - Page 1 of 2





**Thread Class:** 2a **Thread Direction: Right-hand Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Gray **Body Style:** Threaded bushing mounted **Overall Length:** 1.000 inches Mounting Bushing Length: 0.375 inches **Body Length:** 0.500 inches **Overall Diameter:** 0.406 inches **Bushing Accommodation Hole Shape:** Round Maximum Voltage Rating In Volts: 2000.0 ac Accommodated Finger Type: Test prod single finger **Finger Accommodation Diameter:** 0.080 inches single finger Finger Accommodation Length: 0.563 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.250 inches **Current Rating In Amps:** 5.0 Mounting Facility Type And Quantity: 1 bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.250 inches **Terminal Type:** Tab, solder lug Material: Plastic insulator

# NSN 5935-00-880-3929

Tip Jack - Page 2 of 2



Material:

Plastic insulator

#### Precious Material And Location:

Contact surface gold

## Precious Material:

Gold

### Surface Treatment:

Gold contact

### Surface Treatment:

Gold contact

#### **Test Data Document:**

96906-ms16108 standard (includes industry or association standards, individual manufactureer standards, etc.).

#### **Thread Series Designator:**

Unef

#### **Specification Data:**

96906-ms16108-9c government standard

#### Shelf Life:

N/a

#### Unit Of Measure:

---

# Demilitarization:

No

#### Fiig:

A03400