Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-880-5441

## Body Style:

Straight shape

### **Overall Length:**

Between 1.198 inches and 1.228 inches

#### **Overall Height:**

0.676 inches

#### **Overall Width:**

Between 0.479 inches and 0.509 inches

#### **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

#### Distance Between Mounting Facility Centers:

Between 0.979 inches and 0.989 inches

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

9 single mating end

#### Contact Removability:

Nonremovable single mating end single contact grouping

#### Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

#### Polarization Method:

Mating end

## Shell Type:

Solid

## Terminal Location:

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

## Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

## Insert Material:

Plastic diallyl phthalate single mating end

## **Terminal Type:**

Solder well single mating end single contact grouping

## Shell Material:

Steel

## Shell Surface Treatment:

Cadmium and chromate

# Insert Material Specification:

Mil-p-19833, type gdi-30f military specification single material response single mating end

# Included Contact Quantity:

9 single mating end single contact grouping

# NSN 5935-00-880-5441

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type: Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.009 gold grains, troy and 0.009 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-p-19833 spec.