NSN 5935-00-880-5842

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-880-5842

Body Style:

Straight edge type

Overall Length:

Between 1.840 inches and 1.860 inches

Overall Height:

Between 0.650 inches and 0.670 inches

Overall Width:

Between 0.314 inches and 0.329 inches

Unthreaded Mounting Hole Diameter:

Between 0.111 inches and 0.121 inches

Distance Between Mounting Facility Centers:

Between 1.530 inches and 1.544 inches

Board Accommodated Width:

Between 0.054 inches and 0.071 inches

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Copper single mating end single contact grouping and gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-c-14550, class 4 military specification 1st treatment response single mating end single contact grouping and mil-g-45204, type 1, class 2 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Contact Material Specification:

Astm b103 alloy c assn standard single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-19833, type gdi-30 military specification single material response single mating end

Included Contact Quantity:

6 single mating end single contact grouping

Included Contact Type:

Spring pincers single mating end single contact grouping

Precious Material And Location:

Contact surface gold

NSN 5935-00-880-5842

Electrical Receptacle Connector - Page 2 of 2



Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Demilitarization:
No

Mil-std (military Standard):

Mil-c-14550 spec.