## NSN 5935-00-880-7001



Receptacle Dummy Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-880-7001 **Overall Length:** 0.650 inches **Overall Height:** 1.703 inches Overall Width: 1.703 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.375 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.375 inches **Distance From Mounting Shoulder To Front Face:** Between 0.556 inches and 0.587 inches **Mating End Quantity:** 1 **Shell Type:** Solid **Connector Locking Method:** Bayonet pin **End Application:** Fms-a7 aircraft; f4s aircraft, orion p-3; helicopter, carrier based asw, sh-60f; aircraft, stratofortress b-52; aircrdaft, f-16; guided missile, intercept; aircraft, eagle f-15; aircraft, thunderbolt ii, a-10 **Criticality Code Justification:** Feat **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response

#### **Special Features:**

Weapon system essential

#### **Test Data Document:**

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

96906-ms3115 government standard

#### Shelf Life:

N/a

### **Unit Of Measure:**

# NSN 5935-00-880-7001

Receptacle Dummy Connector - Page 2 of 2



em			

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-26482 spec.