Receptacle Dummy Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-880-7001

Overall Length:	
0.650 inches	
Overall Height:	
1.703 inches	
Overall Width:	
1.703 inches	
Environmental Pro	ection:
Moisture resistant a	nd salt water resistant and vibration resistant
Unthreaded Mount	ng Hole Diameter:
0.120 inches	
Center To Center I	istance Between Mounting Facilities Parallel To Height:
1.375 inches	
Distance Between	Centerlines Of Mounting Facilities Parallel To Body Width:
1.375 inches	
Distance From Mo	Inting Shoulder To Front Face:
Between 0.556 inch	es and 0.587 inches
Mating End Quant	y:
1	
Shell Type:	
Solid	
Connector Locking	Method:
Bayonet pin	
End Application:	
Fms-a7 aircraft; f4s	aircraft; aircraft, orion p-3; helicopter, carrier based asw, sh-60f; aircraft, stratofortress b-52; aircrdaft, f-16; guided
missile, intercept;	ircraft, eagle f-15; aircraft, thunderbolt ii, a-10
Criticality Code Ju	stification:
Feat	
Shell Material:	
Aluminum alloy	
Shell Surface Trea	ment:
Cadmium	
Shell Surface Trea	ment Specification:
Qq-p-416, type 2, c	3 federal specification single treatment response
Special Features:	
Weapon system ess	ential
Test Data Docume	it:
81349-mil-c-26482	pecification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes co	mmercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and p	erformance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data	
96906-ms3115 gov	rnment standard
Shelf Life:	
N/a	
Unit Of Measure:	

Receptacle Dummy Connector - Page 2 of 2



Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-26482 spec.