NSN 5935-00-880-7894

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-880-7894 **Overall Length:** 1.552 inches **Overall Height:** 1.141 inches Overall Width: **1.141** inches **Environmental Protection:** Salt water resistant and vibration resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches **Mating End Quantity: Contact Position Arrangement Style:** 14-19 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet latch **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:**

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

NSN 5935-00-880-7894

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
19 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.109 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-26482 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0

7100000

Mil-std (military Standard):

Mil-c-26482 spec.