Electrical Connector Backshell - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-00-880-8662

Tried Diss: Dis Constant of C		
Tread Direction:         Left-hand         Seal Matrial:         Rubber         Rubber         Rubber         Stry Inches         Overall Diameter:         1.438 Inches         Cable Opening Diameter:         Between 0.005 Inches and 0.099 Inches         Cable Opening Quantity:         1         State Seature         Mounting Facility Type And Quantity:         1         State Add coupling         Mounting Facility Type And Quantity:         1 threadd coupling         State Teatment:         Andrize         State Teatment:         Andrize         Andrize         Interderention:         Andrize         Int Colessenei </th <th>Thread Class:</th> <th></th>	Thread Class:	
Lefthand         Stel Material:         Rubber         Overall Length:         3.973 Inches         Overall Diameter:         1.438 Inches         Cable Opening Diameter:         Between 0.605 Inches and 0.699 Inches         Cable Opening Diameter:         1         Staff Type:         Cable Opening Cuantity:         1         1         Staff Type:         Casket         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Oxy Per Inch (pt):         18         Thread Staff         Aurial:         Aurial:         Aurial:         Aurial:         Stafface Treatment:         Andrize         Stright Shape solid type         Stright Shape solid type         Stright Shape solid type         Stright Shape solid type         Check Stright Shape solid type         Stright Shape solid type         Stright Shape solid type         Check Stright Shape solid type         Stright Shape solid type         Stright Shape solid type         Check Stright Stright Shape solid type		
Seal Material:         Rubber         Overall Length:         3.979 Inches         Overall Dimeter:         1.438 Inches         Cable Opening Diameter:         1.438 Inches and 0.699 Inches         Cable Opening Quantity:         Cable Opening Quantity:         1         Sear Type:         Gasket         Mounting Facility Type And Quantity:         1         Thready Oper Inch (pi):         18         Thread Quart Per Inch (pi):         1.250 Inches         Aumium alloy         Surface Treatment:         Anodized         Stripter Shape solid type         Stripter Shape solid type         Stripter Shape solid type         Chard Streatment:         Anodized         Stripter Shape solid type         Stripter Strapter Streatment:         Incol         Chard Streate Designator:         No         Stripter Strapter Streatment:         Incol         Incol         Stripter Strapter Streatment:         Incol         Incol Streatment:         Incol Streatment:         Incol Streatment:     <		
Rubber         Overall Length:         3.979 inches         Syle prince         Syle prince         1.438 inches         Cable Opening Diameter:         Between 0.605 inches and 0.699 inches         Cable Opening Quantity:         1         Salst         Gasket         Monting Facility Type And Quantity:         1 threaded coupling         Thread Size:         1.250 inches         1.250 inches         Matrial:         Aurinum alloy         Surface Treatment:         Andrize         Stradge Signator:		
Overal Length:3.979 inchesSourd Diameter:1.438 inchesCable Opening Diameter:Between 0.005 inches and 0.699 inchesCable Opening Quantity:1Seat Type:GasketMounting Facility Type And Quantity:1 threaded couplingThready Qy Per Inch (tpi):181.250 inchesMarting Facility Type And Quantity:1 threaded couplingThready Qy Per Inch (tpi):1828SubreadMarting:1.250 inchesSuffaceSuffaceSuffaceSuffaceSyle Designator:Stright shape solid typeCharletAndazedSuffaceSuffac		
3.979 inchesOverall Diameter:1.438 inchesCable Opening Diameter:Between 0.605 inches and 0.699 inchesCable Opening Quantity:Cable Opening Quantity:1Sear Type:GasketMonting Facility Type And Quantity:1 threaded couplingThready Qty Per Inch (tpl):1819Cable Opening Diameter:1.250 inchesMarcial:1.250 inchesSurface Treatment:1.250 inchesMarcial:1.250 inchesMarcial:1.250 inches1.250 inches <t< th=""><th></th><th></th></t<>		
Overall Diameter:1.438 inchesCable Opening Diameter:Between 0.605 inches and 0.699 inchesCable Opening Quantity:Cable Opening Quantity:1Seal Type:GaskatMounting Facility Type And Quantity:1 threaded couplingThready Qty Per Inch (tpl):18Threaded Size:1.250 inchesMaterial:Atuminum alloySurface Treatment:AnodizeStrateg State St		
1438 incles         Cable Opening Diameter:         Between 0.605 inches and 0.699 inches         Cable Opening Quantity:         1         Seaf Type:         Gasket         Mounting Eacliity Type And Quantity:         1 threaded coupling         Thready Oty Per Inch (tpi):         18         Thread Size:         1.250 inches         Material:         Atuminum alloy         Surface Treatment:         Anodize         Stripte Designator:         Stripte Signator:         Intread Size:         Anodize         Surface Treatment:         Anodize         Stripte Signator:         Intread Size:         Anodize         Surface Treatment:         Anodize         Stripte Signator:         Interd Series Designator:         Interd Series Designator:         Interd Series Designator:         Interd Series Designator:         Na         Stripte Signator:         Interd Series Designator:         Interd Series Designator:         Interd Series Designator:         Na         Stripte Series Designator:<		
Cable Opening Quantity:         Cable Opening Quantity:         1         Seal Type:         Cable Opening Quantity:         Gaskot         Mounting Facility Type And Quantity:         1         Thready Coupling         Thready Coupling         Thready Coupling         Thready Coupling         Thready Coupling         Thready State:         1.250 inches         Material:         Aldrinium alloy         Surface Treatment:         Anodize         Style Designator:         Straight shape solid type         Andized         Thread Streise Designator:         Indicad         Thread Streise Designator:         Carde Treatment:         Anodized         Thread Streise Designator:         Indicad         Thread Streise Designator:         Indicad         Thread Streise Designator:         Indication:         Indication:         Indication:         Indication:         Indication:         Indication:         Indication:         Indication:         Indication: <th></th> <th></th>		
Between 0.605 inches and 0.699 inches         Cable Opening Quantity:         1         Seal Type:         Gasket         Moning Facility Type And Quantity:         1 threaded coupling         Thready Qty Per Inch (tpi):         18         Thread Size:         1.250 inches         Material:         Aurninum alloy         Strate Treatment:         Anodize         Strade Tossi State:         Strade Tossi State:         Aurdized         Strade Tossi State:         Anodize         Strade Tossi State:         Anodized         Thread		
Cable Opening Quantity:         1         Seal Type:         Gasket         Mounting Facility Type And Quantity:         1 threaded coupling         Threaded coupling         Threaded soupling         Threaded soupling         Threaded soupling         Autoritum         10         12         13         Thread Size:         1.250 inches         Material:         Adurnium alloy         Surface Treatment:         Anodize         Straight shape solid type         Straight shape solid type         Anodized         Thread Series Designator:         Linef         Straight Shape solid type         Straight Shape solid type         Chord Series Designator:         Linef         Straight Shape solid type		
1         Seal Type:         Gasket         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Oty Per Inch (tpi):         18         Thread Size:         1.250 inches         Adurnium alloy         Surface Treatment:         Anodize         Stright shape solid type         Stright shape solid type         Anodized         Thread Series Designator:         Information:         Anodized         Thread Series Designator:         Information:         Information: <th></th> <th></th>		
Seal Type:GaskatMounting Facility Type And Quantity:1 threaded couplingThreaded couplingThready Qty Per Inch (tpi):18Thread Size:1.250 inchesMaterial:Autonium alloySurface Treatment:AnodizeStraight shape solid typeSurface Treatment:AnodizedBurdace Treatment:AnodizedSurface Treatment:AnodizedStraight shape solid typeSurface Treatment:AnodizedThread Series Designator:UnefShelf Life:NaDuit of Measure:Fmelliatrization:NoFig:	Cable Opening Quantity:	
Gasket         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Qty Per Inch (tpi):         18         Thread Size:         1.250 inches         Material:         Atterial:         Atterial:         Atterial:         Auminum alloy         Surface Treatment:         Anodize         Style Designator:         Straight shape solid type         Straface Treatment:         Anodized         Burdiad:         Straface Treatment:         Anodized         Burdiad Strafage Solid type         Straface Treatment:         Anodized         Thread Series Designator:         Unef         Sheff Life:         N/a         Chi Of Measure:            Fomiliatization:         No         Fig:	1	
Mounting Facility Type And Quantity:         1 threaded coupling         Thready Quy Per Inch (tpi):         18         Thread Size:         1.250 inches         Material:         Aluminum alloy         Surface Treatment:         Anodize         Stright shape solid type         Stright shape solid type         Anodized         Thread Series Designator:         Anodized         Strifee Treatment:         Anodized         Strifee Treatment:         Anodized         Strifee Treatment:         Anodized         Thread Series Designator:         Unef         Sheff Life:         Na         Dit Of Measure:         Image:         No         Fig:		
1 threaded coupling         Thready Qty Per Inch (tpi):         18         Thread Size:         1.250 inches         Material:         Auminum alloy         Surface Treatment:         Anodize         Style Designator:         Straight shape solid type         Strafee Treatment:         Anodized         Thread Series Designator:         Unef         Sheff Life:         Na         Lift Of Measure:         Image:         No         Fig:	Gasket	
Thready Qty Per Inch (tpi):18Thread Size:1.250 inchesMaterial:Aluminum alloySurface Treatment:AnodizeStyle Designator:Stright shape solid typeStright shape solid typePondizedThread Series Designator:UnefSheff Life:NaDuffDir of Measure:Int of Measure:Int of Measure:NaFemilitarization:NoFig:Stig:	Mounting Facility Type And Quantity:	
18         Thread Size:         1.250 inches         Material:         Aluminum alloy         Surface Treatment:         Anodize         Style Designator:         Straight shape solid type         Straige Treatment:         Anodized         Bread Series Designator:         Unef         Sheff Life:         Na         Unef         Sheff Life:         Na         Dit Of Measure:         -         Peniltarization:         Na         Fig:	1 threaded coupling	
Hread Size:1.250 inchesMaterial:Aluminum alloyAuface Treatment:AnodizeStright shape solid typeStright shape solid typeSurface Treatment:AnodizedThread Series Designator:UnefShelf Life:NaDeniltarization:ToFormiltarization:NoFig:	Thready Qty Per Inch (tpi):	
1.250 inchesMaterial:Aluminum alloySurface Treatment:AnodizeStyle Designator:Straight shape solid typeSurface Treatment:AnodizedThread Series Designator:UnefShelf Life:N/aDin of Measure:Demilitarization:NoFig:	18	
Material:Aluminum alloySurface Treatment:AnodizeStyle Designator:Straight shape solid typeSurface Treatment:AnodizedThread Series Designator:UnefSheff Life:N/aDint of Measure:-Pomilitarization:NoFig:	Thread Size:	
Aluminum alloySurface Treatment:AnodizeStyle Designator:Straight shape solid typeSurface Treatment:AnodizedThread Series Designator:UnefShelf Life:N/aDint Of Measure:-Pomilitarization:NoFig:	1.250 inches	
Surface Treatment:AnodizeStyle Designator:Straight shape solid typeSurface Treatment:AnodizedThread Series Designator:UnefShelf Life:N/aDint Of Measure:Demilitarization:NoFig:	Material:	
Anodize Style Designator: Straight shape solid type Surface Treatment: Anodized Thread Series Designator: Unef Shelf Life: N/a Unt Of Measure: Fig:	Aluminum alloy	
Style Designator:Straight shape solid typeSurface Treatment:AnodizedThread Series Designator:UnefShelf Life:N/aUnt Of Measure:Demilitarization:NoFig:	Surface Treatment:	
Straight shape solid typeSurface Treatment:AnodizedThread Series Designator:UnefShelf Life:N/aUnt Of Measure:Demilitarization:NoFig:	Anodize	
Surface Treatment: Anodized Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Style Designator:	
Anodized Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No	Straight shape solid type	
Thread Series Designator:   Unef   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:	Surface Treatment:	
Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Anodized	
Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:	Thread Series Designator:	
N/a Unit Of Measure: Demilitarization: No Fiig:	Unef	
Unit Of Measure:  Demilitarization: No Fiig:	Shelf Life:	
 Demilitarization: No Fiig:	N/a	
No Fiig:	Unit Of Measure:	
No Fiig:		
Fiig:	Demilitarization:	
	No	
A10100	Fiig:	
	A10100	