

View Online at <https://aerobasegroup.com/nsn/5935-00-881-6402>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

T-shape

**Overall Length:**

1.220 inches

**Environmental Protection:**

Heat resistant and moisture proof and vibration resistant

**Threaded Device Type:**

Mounting bushing

**Mating End Quantity:**

3

**Contact Position Arrangement Style:**

Nonstd all mating ends

**Contact Removability:**

Nonremovable all mating ends all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 all mating ends all contact groupings

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Thread Size:**

0.312 inches

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:**

Gold all mating ends all contact groupings and silver all mating ends all contact groupings

**Insert Material:**

Plastic polytetrafluoroethylene all mating ends

**Contact Material Specification:**

Qq-b-626, comp 22 federal specification single material response all mating ends single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Silver

**Shell Surface Treatment Specification:**

Qq-s-365, type 2, gr a federal specification single treatment response

**Shell Material Specification:**

Qq-b-626, comp 22 federal specification single material response

**Insert Material Specification:**

Mil-p-19468 military specification single material response all mating ends

**Included Contact Quantity:**

3 all mating ends single contact grouping

**Bushing Accommodation Hole Shape:**

Round

**Included Contact Type:**

Coaxial pin all mating ends all contact groupings

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver and shell surfaces silver

**Precious Material And Weight:**

0.015 gold grains, troy and 0.030 silver grains, troy

**Precious Material:**

Gold and silver

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-p-19468 spec.