

View Online at <https://aerobasegroup.com/nsn/5935-00-881-6402>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

T-shape

Overall Length:

1.220 inches

Environmental Protection:

Heat resistant and moisture proof and vibration resistant

Threaded Device Type:

Mounting bushing

Mating End Quantity:

3

Contact Position Arrangement Style:

Nonstd all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

500.0 all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thread Size:

0.312 inches

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends all contact groupings and silver all mating ends all contact groupings

Insert Material:

Plastic polytetrafluoroethylene all mating ends

Contact Material Specification:

Qq-b-626, comp 22 federal specification single material response all mating ends single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Shell Surface Treatment Specification:

Qq-s-365, type 2, gr a federal specification single treatment response

Shell Material Specification:

Qq-b-626, comp 22 federal specification single material response

Insert Material Specification:

Mil-p-19468 military specification single material response all mating ends

Included Contact Quantity:

3 all mating ends single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Coaxial pin all mating ends all contact groupings

Precious Material And Location:

Contact surfaces gold and contact surfaces silver and shell surfaces silver

Precious Material And Weight:

0.015 gold grains, troy and 0.030 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19468 spec.