

View Online at <https://aerobasegroup.com/nsn/5935-00-882-2800>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Overall Length:**

0.812 inches

**Overall Diameter:**

0.249 inches

**Distance From Mounting Shoulder To Front Face:**

0.508 inches

**Mounting Facility Thickness:**

0.200 inches

**Threaded Device Type:**

Mounting bushing

**Mating End Quantity:**

2

**Contact Maximum Current Rating In Amps:**

1.5 all mating ends all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

400.0 all mating ends all contact groupings

**Shell Type:**

Solid

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends all contact groupings

**Thread Length:**

0.263 inches

**Thread Size:**

0.190 inches

**Contact Material:**

Copper alloy all mating ends all contact groupings

**Contact Surface Treatment:**

Gold all mating ends all contact groupings

**Insert Material:**

Plastic tetrafluoroethylene all mating ends

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 2 military specification single treatment response all mating ends all contact groupings

**Contact Material Specification:**

Qq-c-530, comp ht federal specification single material response all mating ends all contact groupings

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Gold

**Shell Surface Treatment Specification:**

Mil-g-45204, type 2, cl 2 military specification single treatment response

**Shell Material Specification:**

Qq-b-626, comp 22 federal specification single material response

**Included Contact Quantity:**

1 all mating ends all contact groupings

**Bushing Accommodation Hole Shape:**

Round

**Included Contact Type:**

Round socket all mating ends all contact groupings

**Precious Material And Location:**

Contact surfaces and shell surfaces gold

**Precious Material And Weight:**

0.110 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.