Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-882-8957

2a         Treac Direction:         Left-hand         Body Style:         Straight shape, external coupling         Overall Length:         Between 1.481 inches and 1.603 inches         Overall Height:         Between 2.480 inches and 2.520 inches         Overall Width:         Between 2.480 inches and 2.520 inches         Environmental Protection:         Vibration resistant         Unthreaded Mounting Hole Diameter:         Between 0.207 inches and 0.213 inches         Center To Center Distance Between Mounting Facilities Parallel To Height:         Between 1.933 inches and 1.943 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         Between 1.933 inches and 1.943 inches         Distance From Mounting Shoulder To Front Face:         Between 1.933 inches and 1.943 inches         Distance From Mounting Shoulder To Front Face:         Between 0.875 inches and 0.891 inches         Threaded Device Type:         Coupling facility         Maing End Quantity:         1         Contact Removability:         Nonremovable single mating end all contact groupings         Contact Maximum Cu Otlage Rating In Volts:         20.0 single mating end all contact groupings	Thread Class:
Left-hand         Body Style:         Straight shape, external coupling         Overall Length:         Between 1.461 inches and 1.603 inches         Overall Height:         Between 2.480 inches and 2.520 inches         Overall Widt:         Between 2.480 inches and 2.520 inches         Environmental Protection:         Vibration resistant         Unthreaded Mounting Hole Diameter:         Between 0.207 inches and 0.213 inches         Cotter To Center Distance Between Mounting Facilities Parallel To Height:         Between 1.933 inches and 1.943 inches         Distance Between Conterlines Of Mounting Facilities Parallel To Body Width:         Between 0.875 inches and 0.891 inches         Distance From Mounting Shoulder To Front Face:         Between 0.875 inches and 0.891 inches         Threaded Device Type:         Coupling facility         Mating End Quantity:         1         Contact Position Arrangement Style:         36-9 single mating end all contact groupings         Contact Removability:         Nonremovable single mating end all contact groupings         Contact Maximum Current Rating In Amps:         80.0 single mating end all contact groupings         Contact Maximum Curvet Rating In Votts:         700.0	2a
Body Syle:         Straight shape, external coupling         Overall Length:         Between 1.461 inches and 1.603 inches.         Overall Height:         Between 2.480 inches and 2.520 inches         Overall Width:         Between 2.480 inches and 2.520 inches         Environmental Protection:         Vibration resistant         Unthreaded Mounting Hole Diameter:         Between 0.207 inches and 0.213 inches         Center To Center Distance Between Mounting Facilities Parallel To Height:         Between 1.933 inches and 1.943 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         Between 1.933 inches and 1.943 inches         Distance From Mounting Soulder To Front Face:         Between 0.875 inches and 0.891 inches         Threaded Device Type:         Coupling facility         Mating End Quantity:         1         Contact Removability:         Nonremovable single mating end all contact groupings         Contact Maximum Current Rating In Amps:         80.0 single mating end all contact groupings         Contact Maximum Curter Rating In Volts:         200.0 single mating end all contact groupings         Contact Maximum Curvet Rating In Volts:         200.0 single mating end all contact grouping	Thread Direction:
Straight shape, external coupling         Overall Length:         Between 1.461 inches and 1.603 inches         Overall Height:         Between 2.480 inches and 2.520 inches         Overall Width:         Between 2.480 inches and 2.520 inches         Environmental Protection:         Vibration resistant         Untreaded Mounting Hole Diameter:         Between 0.207 inches and 0.213 inches         Center To Center Distance Between Mounting Facilities Parallel To Height:         Between 1.933 inches and 1.943 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         Between 0.875 inches and 0.891 inches         Distance From Mounting Shoulder To Front Face:         Between 0.875 inches and 0.891 inches         Threaded Device Type:         Coupling facility         Mating End Quantity:         1         Contact Position Arrangement Style:         36-9 single mating end         Contact Maximum Current Rating In Amps:         80.0 single mating end 1st contact groupings         Contact Maximum Curters Rating In Volts:         200.0 single mating end all contact groupings         Contact Maximum Cu Voltage Rating In Volts:         200.0 single mating end all contact groupings         Contact Maximum Cu Vo	Left-hand
Straight shape, external coupling         Overall Length:         Between 1.461 inches and 1.603 inches         Overall Height:         Between 2.480 inches and 2.520 inches         Overall Width:         Between 2.480 inches and 2.520 inches         Environmental Protection:         Vibration resistant         Unthreaded Mounting Hole Diameter:         Between 0.207 inches and 0.213 inches         Center To Center Distance Between Mounting Facilities Parallel To Height:         Between 1.933 inches and 1.943 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         Between 0.875 inches and 0.891 inches         Distance From Mounting Shoulder To Front Face:         Between 0.875 inches and 0.891 inches         Threaded Device Type:         Coupling facility         Mating End Quantis:         1         Contact Position Arrangement Style:         36-9 single mating end         Contact Maximum Current Rating In Amps:         80.0 single mating end 1st contact groupings         Contact Maximum Curters Rating In Volts:         20.0. single mating end all contact groupings         Contact Maximum Cu Voltage Rating In Volts:         20.0. single mating end all contact groupings         Contact Maximum Cu Vo	Body Style:
Overall Length:         Between 1.461 inches and 1.603 inches         Overall Height:         Between 2.480 inches and 2.520 inches         Overall Width:         Between 2.480 inches and 2.520 inches         Environmental Protection:         Vibration resistant         Unthreaded Mounting Hole Diameter:         Between 0.207 inches and 0.213 inches         Center To Center Distance Between Mounting Facilities Parallel To Height:         Between 1.933 inches and 1.943 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         Between 0.875 inches and 0.891 inches         Distance Between 0.875 inches and 0.891 inches         Between 0.875 inches and 0.891 inches         Threaded Device Type:         Coupling facility         Mating End Quantity:         1         Contact Position Arrangement Style:         36-9 single mating end         Contact Renovability:         Nonremovable single mating end all contact groupings         Contact Maximum Current Rating In Amps:         80.0 single mating end 1st contact groupings         Contact Maximum Curvet Rating In Volts:         200.0 single mating end all contact groupings         Contact Maximum De Voltage Rating In Volts:         200.0 single mating end al	
Between 1.401 inches and 1.603 inches         Overall Height:         Between 2.480 inches and 2.520 inches         Overall Width:         Between 2.480 inches and 2.520 inches         Environmental Protection:         Vibration resistant         Unthreaded Mounting Hole Diameter:         Between 0.207 inches and 0.213 inches         Center To Center Distance Between Mounting Facilities Parallel To Height:         Between 1.933 inches and 1.943 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         Between 1.933 inches and 1.943 inches         Distance From Mounting Shoulder To Front Face:         Between 0.875 inches and 0.891 inches         Threaded Device Type:         Coupling facility         Mating End Quantity:         1         Contact Position Arrangement Style:         36-9 single mating end         Contact Raximum Current Rating In Amps:         80.0 single mating end all contact groupings         Contact Maximum Curvent Rating In Motis:         20.0 single mating end all contact groupings         Contact Maximum Dc Voltage Rating In Volts:         20.0 single mating end all contact groupings         Polarization Method:         Reyway or multiple keyway         Insert Position In Deg: </td <td></td>	
Between 2.480 inches and 2.520 inches         Overall Width:         Between 2.480 inches and 2.520 inches         Environmental Protection:         Vibration resistant         Unthreaded Mounting Hole Diameter:         Between 0.207 inches and 0.213 inches         Center To Center Distance Between Mounting Facilities Parallel To Height:         Between 1.933 inches and 1.943 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         Between 1.933 inches and 1.943 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         Between 0.875 inches and 0.891 inches         Threaded Device Type:         Coupling facility         Mating End Quantity:         1         Contact Position Arrangement Style:         36-9 single mating end all contact groupings         Contact Removability:         Nonremovable single mating end all contact groupings         Contact Maximum Current Rating In Amps:         80.0 single mating end all contact groupings         Contact Maximum C Voltage Rating In Volts:         700.0 single mating end all contact groupings         Polarization Method:         Keyway or multiple keyway         Heyser or multiple keyway         Boui         Bou Meth	-
Overall Width:         Between 2.480 inches and 2.520 inches         Environmental Protection:         Vibration resistant         Unthreaded Mounting Hole Diameter:         Between 0.207 inches and 0.213 inches         Center To Center Distance Between Mounting Facilities Parallel To Height:         Between 1.933 inches and 1.943 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         Between 1.933 inches and 1.943 inches         Distance From Mounting Shoulder To Front Face:         Between 0.875 inches and 0.891 inches         Threaded Device Type:         Coupling facility         Mating End Quantity:         1         Contact Position Arrangement Style:         36-9 single mating end         Contact Removability:         Nonremovable single mating end all contact groupings         Contact Maximum Current Rating In Amps:         80.0 single mating end 1st contact groupings         Contact Maximum Ac Voltage Rating In Volts:         200.0 single mating end all contact groupings         Polarization Method:         Keyway or multiple keyway         Insert Position In Deg:         80.0	Overall Height:
Between 2.480 inches and 2.520 inches Environmental Protection: Vibration resistant Unthreaded Mounting Hole Diameter: Between 0.207 inches and 0.213 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.933 inches and 1.943 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.933 inches and 1.943 inches Distance From Mounting Shoulder To Front Face: Between 0.875 inches and 0.891 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 36-9 single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 80.0 single mating end 1st contact groupings Contact Maximum Ac Voltage Rating In Volts: 200.0 single mating end all contact groupings Polarization Method: Keyway or multiple keyway Insert Position In Deg: 80.0 Shell Type:	Between 2.480 inches and 2.520 inches
Environmental Protection: Vibration resistant Unthreaded Mounting Hole Diameter: Between 0.207 inches and 0.213 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.933 inches and 1.943 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.933 inches and 1.943 inches Distance From Mounting Shoulder To Front Face: Between 0.875 inches and 0.891 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 36-9 single mating end Contact Position Arrangement Style: 36-9 single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 80.0 single mating end 1st contact groupings Contact Maximum Ac Voltage Rating In Volts: 200.0 single mating end all contact groupings Polarization Method: Keyway or multiple keyway Insert Position In Deg: 80.0 Shell Type:	Overall Width:
Vibration resistant         Unthreaded Mounting Hole Diameter:         Between 0.207 inches and 0.213 inches         Center To Center Distance Between Mounting Facilities Parallel To Height:         Between 1.933 inches and 1.943 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         Between 1.933 inches and 1.943 inches         Distance From Mounting Shoulder To Front Face:         Between 0.875 inches and 0.891 inches         Threaded Device Type:         Coupling facility         Mating End Quantity:         1         Contact Position Arrangement Style:         36-9 single mating end         Contact Removability:         Nonremovable single mating end all contact groupings         Contact Maximum Current Rating In Amps:         80.0 single mating end 1st contact groupings         Contact Maximum Ac Voltage Rating In Volts:         70.0 single mating end all contact groupings         Polarization Method:         Keyway or multiple keyway         Insert Position In Deg:         80.0         Stell Type:	Between 2.480 inches and 2.520 inches
Unthreaded Mounting Hole Diameter:         Between 0.207 inches and 0.213 inches         Center To Center Distance Between Mounting Facilities Parallel To Height:         Between 1.933 inches and 1.943 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         Between 1.933 inches and 1.943 inches         Distance From Mounting Shoulder To Front Face:         Between 0.875 inches and 0.891 inches         Threaded Device Type:         Coupling facility         Mating End Quantity:         1         Contact Position Arrangement Style:         36-9 single mating end         Contact Removability:         Nonremovable single mating end all contact groupings         Contact Maximum Current Rating In Amps:         80.0 single mating end all contact groupings         Contact Maximum Dc Voltage Rating In Volts:         200.0 single mating end all contact groupings         Polarization Method:         Keyway or multiple keyway         Insert Position In Deg:         80.0         Sile Type:	Environmental Protection:
Between 0.207 inches and 0.213 inches         Center To Center Distance Between Mounting Facilities Parallel To Height:         Between 1.933 inches and 1.943 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         Between 1.933 inches and 1.943 inches         Distance From Mounting Shoulder To Front Face:         Between 0.875 inches and 0.891 inches         Threaded Device Type:         Coupling facility         Mating End Quantity:         1         Contact Position Arrangement Style:         36-9 single mating end         Contact Removability:         Nonremovable single mating end all contact groupings         Contact Maximum Current Rating In Amps:         80.0 single mating end 1ls contact groupings         Contact Maximum Current Rating In Volts:         700.0 single mating end all contact groupings         Contact Maximum Curvent Rating In Volts:         700.0 single mating end all contact groupings         Polarization Method:         Keyway or multiple keyway         Insert Position In Deg:         80.0         Shell Type:	Vibration resistant
Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.933 inches and 1.943 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.933 inches and 1.943 inches Distance From Mounting Shoulder To Front Face: Between 0.875 inches and 0.891 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 36-9 single mating end Contact Position Arrangement Style: 36-9 single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 80.0 single mating end 1st contact grouping Contact Maximum Ac Voltage Rating In Volts: 200.0 single mating end all contact groupings Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end all contact groupings Polarization Method: Keyway or multiple keyway Insert Position In Deg: 80.0 Shell Type:	Unthreaded Mounting Hole Diameter:
Between 1.933 inches and 1.943 inches         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         Between 1.933 inches and 1.943 inches         Distance From Mounting Shoulder To Front Face:         Between 0.875 inches and 0.891 inches         Threaded Device Type:         Coupling facility         Mating End Quantity:         1         Contact Position Arrangement Style:         36-9 single mating end         Contact Removability:         Nonremovable single mating end all contact groupings         Contact Maximum Current Rating In Amps:         80.0 single mating end all contact groupings         Contact Maximum Current Rating In Volts:         200.0 single mating end all contact groupings         Contact Maximum Dc Voltage Rating In Volts:         200.0 single mating end all contact groupings         Polarization Method:         Keyway or multiple keyway         Insert Position In Deg:         80.0         Shell Type:	Between 0.207 inches and 0.213 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.933 inches and 1.943 inches Distance From Mounting Shoulder To Front Face: Between 0.875 inches and 0.891 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 36-9 single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 80.0 single mating end 1st contact grouping Contact Maximum Ac Voltage Rating In Volts: 200.0 single mating end all contact groupings Contact Maximum Dc Voltage Rating In Volts: 200.0 single mating end all contact groupings Contact Maximum Dc Voltage Rating In Volts: 200.0 single mating end all contact groupings Polarization Method: Keyway or multiple keyway Insert Position In Deg: 80.0 Shell Type:	Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.933 inches and 1.943 inchesDistance From Mounting Shoulder To Front Face:Between 0.875 inches and 0.891 inchesThreaded Device Type:Coupling facilityMating End Quantity:1Contact Position Arrangement Style:36-9 single mating endContact Removability:Nonremovable single mating end all contact groupingsContact Maximum Current Rating In Amps:80.0 single mating end 1st contact groupingsContact Maximum Ac Voltage Rating In Volts:200.0 single mating end all contact groupingsContact Maximum Dc Voltage Rating In Volts:700.0 single mating end all contact groupingsPolarization Method:Keyway or multiple keywayInsert Position In Deg:80.0Shell Type:	Between 1.933 inches and 1.943 inches
Distance From Mounting Shoulder To Front Face:Between 0.875 inches and 0.891 inchesThreaded Device Type:Coupling facilityMating End Quantity:1Contact Position Arrangement Style:36-9 single mating endContact Removability:Nonremovable single mating end all contact groupingsContact Maximum Current Rating In Amps:80.0 single mating end 1st contact groupingsContact Maximum Ac Voltage Rating In Volts:200.0 single mating end all contact groupingsContact Maximum Dc Voltage Rating In Volts:700.0 single mating end all contact groupingsPolarization Method:Keyway or multiple keywayInsert Position In Deg:80.0Shell Type:	Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.875 inches and 0.891 inchesThreaded Device Type:Coupling facilityMating End Quantity:1Contact Position Arrangement Style:36-9 single mating endContact Removability:Nonremovable single mating end all contact groupingsContact Maximum Current Rating In Amps:80.0 single mating end 1st contact groupingsContact Maximum Ac Voltage Rating In Volts:200.0 single mating end all contact groupingsContact Maximum Dc Voltage Rating In Volts:700.0 single mating end all contact groupingsPolarization Method:Keyway or multiple keywayInsert Position In Deg:80.0Shell Type:	Between 1.933 inches and 1.943 inches
Threaded Device Type:Coupling facilityMating End Quantity:1Contact Position Arrangement Style:36-9 single mating endContact Removability:Nonremovable single mating end all contact groupingsContact Maximum Current Rating In Amps:80.0 single mating end 1st contact groupingsContact Maximum Ac Voltage Rating In Volts:200.0 single mating end all contact groupingsContact Maximum Dc Voltage Rating In Volts:700.0 single mating end all contact groupingsPolarization Method:Keyway or multiple keywayInsert Position In Deg:80.0Shell Type:	Distance From Mounting Shoulder To Front Face:
Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 36-9 single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 80.0 single mating end 1st contact grouping Contact Maximum Ac Voltage Rating In Volts: 200.0 single mating end all contact groupings Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end all contact groupings Polarization Method: Keyway or multiple keyway Insert Position In Deg: 80.0 Shell Type:	Between 0.875 inches and 0.891 inches
Mating End Quantity:         1         Contact Position Arrangement Style:         36-9 single mating end         Contact Removability:         Nonremovable single mating end all contact groupings         Contact Maximum Current Rating In Amps:         80.0 single mating end 1st contact grouping         Contact Maximum Ac Voltage Rating In Volts:         200.0 single mating end all contact groupings         Contact Maximum Dc Voltage Rating In Volts:         700.0 single mating end all contact groupings         Polarization Method:         Keyway or multiple keyway         Insert Position In Deg:         80.0         Shell Type:	Threaded Device Type:
1         Contact Position Arrangement Style:         36-9 single mating end         Contact Removability:         Nonremovable single mating end all contact groupings         Contact Maximum Current Rating In Amps:         80.0 single mating end 1st contact grouping         Contact Maximum Ac Voltage Rating In Volts:         200.0 single mating end all contact groupings         Contact Maximum Dc Voltage Rating In Volts:         700.0 single mating end all contact groupings         Polarization Method:         Keyway or multiple keyway         Insert Position In Deg:         80.0         Shell Type:	Coupling facility
Contact Position Arrangement Style:36-9 single mating endContact Removability:Nonremovable single mating end all contact groupingsContact Maximum Current Rating In Amps:80.0 single mating end 1st contact groupingContact Maximum Ac Voltage Rating In Volts:200.0 single mating end all contact groupingsContact Maximum Dc Voltage Rating In Volts:700.0 single mating end all contact groupingsPolarization Method:Keyway or multiple keywayInsert Position In Deg:80.0Shell Type:	Mating End Quantity:
<ul> <li>36-9 single mating end</li> <li>Contact Removability:</li> <li>Nonremovable single mating end all contact groupings</li> <li>Contact Maximum Current Rating In Amps:</li> <li>80.0 single mating end 1st contact grouping</li> <li>Contact Maximum Ac Voltage Rating In Volts:</li> <li>200.0 single mating end all contact groupings</li> <li>Contact Maximum Dc Voltage Rating In Volts:</li> <li>700.0 single mating end all contact groupings</li> <li>Polarization Method:</li> <li>Keyway or multiple keyway</li> <li>Insert Position In Deg:</li> <li>80.0</li> <li>Shell Type:</li> </ul>	1
Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 80.0 single mating end 1st contact grouping Contact Maximum Ac Voltage Rating In Volts: 200.0 single mating end all contact groupings Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end all contact groupings Polarization Method: Keyway or multiple keyway Insert Position In Deg: 80.0 Shell Type:	Contact Position Arrangement Style:
Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 80.0 single mating end 1st contact grouping Contact Maximum Ac Voltage Rating In Volts: 200.0 single mating end all contact groupings Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end all contact groupings Polarization Method: Keyway or multiple keyway Insert Position In Deg: 80.0 Shell Type:	36-9 single mating end
Contact Maximum Current Rating In Amps: 80.0 single mating end 1st contact grouping Contact Maximum Ac Voltage Rating In Volts: 200.0 single mating end all contact groupings Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end all contact groupings Polarization Method: Keyway or multiple keyway Insert Position In Deg: 80.0 Shell Type:	Contact Removability:
<ul> <li>80.0 single mating end 1st contact grouping</li> <li>Contact Maximum Ac Voltage Rating In Volts:</li> <li>200.0 single mating end all contact groupings</li> <li>Contact Maximum Dc Voltage Rating In Volts:</li> <li>700.0 single mating end all contact groupings</li> <li>Polarization Method:</li> <li>Keyway or multiple keyway</li> <li>Insert Position In Deg:</li> <li>80.0</li> <li>Shell Type:</li> </ul>	Nonremovable single mating end all contact groupings
Contact Maximum Ac Voltage Rating In Volts: 200.0 single mating end all contact groupings Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end all contact groupings Polarization Method: Keyway or multiple keyway Insert Position In Deg: 80.0 Shell Type:	Contact Maximum Current Rating In Amps:
200.0 single mating end all contact groupings Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end all contact groupings Polarization Method: Keyway or multiple keyway Insert Position In Deg: 80.0 Shell Type:	80.0 single mating end 1st contact grouping
Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end all contact groupings Polarization Method: Keyway or multiple keyway Insert Position In Deg: 80.0 Shell Type:	Contact Maximum Ac Voltage Rating In Volts:
700.0 single mating end all contact groupings Polarization Method: Keyway or multiple keyway Insert Position In Deg: 80.0 Shell Type:	200.0 single mating end all contact groupings
Polarization Method: Keyway or multiple keyway Insert Position In Deg: 80.0 Shell Type:	Contact Maximum Dc Voltage Rating In Volts:
Keyway or multiple keyway Insert Position In Deg: 80.0 Shell Type:	700.0 single mating end all contact groupings
Insert Position In Deg: 80.0 Shell Type:	Polarization Method:
80.0 Shell Type:	Keyway or multiple keyway
Shell Type:	Insert Position In Deg:
	80.0
Solid	Shell Type:
	Solid



**Connector Locking Method:** Externally threaded shell **Thread Length:** 0.625 inches Thready Qty Per Inch (tpi): 10 **Thread Size:** 2.250 inches **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Silver single mating end all contact groupings **Insert Material:** Rubber single mating end **Terminal Type:** Solder well single mating end all contact groupings **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Anodize **Included Contact Quantity:** 2 single mating end 2nd contact grouping **Included Contact Type:** Round pin single mating end all contact groupings **Precious Material And Location:** Contact surfaces silver **Precious Material And Weight:** 0.043 silver grains, troy **Precious Material:** Silver **Thread Series Designator:** Double stub Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig:

A039b0