## NSN 5935-00-883-5260

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-883-5260 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.090 inches **Overall Diameter:** 0.500 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet pin Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 32 Thread Size: 0.375 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic tetrafluoroethylene single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Surface Treatment:** 

Silver

**Included Contact Quantity:** 

1 single mating end single contact grouping

## NSN 5935-00-883-5260

Electrical Receptacle Connector - Page 2 of 2



## **Bushing Accommodation Hole Shape:** Round w/flat **Included Contact Type:** Coaxial pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and shell surface silver **Precious Material And Weight:** 0.005 gold grains, troy and 0.100 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef Shelf Life: N/a **Unit Of Measure:** Demilitarization:

No Fiig: A039b0