# NSN 5935-00-883-5966

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-883-5966

Overall Length:
1.328 inches
Overall Height:
1.688 inches
Overall Width:
1.688 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.120 inches and 0.150 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.156 inches and 1.297 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.156 inches and 1.297 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
20-39 single mating end
Contact Removability:
Removable single mating end all contact groupings
Contact Maximum Ac Voltage Rating In Volts:
600.0 single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
252.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings and silver single mating end all contact groupings
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

## NSN 5935-00-883-5966

Electrical Receptacle Connector - Page 2 of 2



Included	Contact	Quantity:
----------	---------	-----------

37 single mating end 2nd contact grouping

### **Included Contact Type:**

Round pin single mating end all contact groupings

### **Precious Material And Location:**

Contact surface gold and contact surface silver

**Precious Material:** 

Gold and silver

#### **Test Data Document:**

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0