Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-883-6838

Thread Class:
2a
Thread Direction:
Right-hand
Overall Height:
1.188 inches
Body Length:
1.266 inches
Body Width:
1.188 inches
Environmental Protection:
Moisture proof
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.906 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.906 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Removability:
Contact Removability:
Contact Removability: Nonremovable single mating end single contact grouping
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps:
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts:
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 200.0 single mating end single contact grouping
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 200.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts:
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 200.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 200.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Connector Locking Method:
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 200.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Connector Locking Method: Externally threaded shell
Contact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:22.0 single mating end single contact groupingContact Maximum Ac Voltage Rating In Volts:200.0 single mating end single contact groupingContact Maximum Dc Voltage Rating In Volts:250.0 single mating end single contact groupingConnector Locking Method:Externally threaded shellThread Size:
Contact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:22.0 single mating end single contact groupingContact Maximum Ac Voltage Rating In Volts:200.0 single mating end single contact groupingContact Maximum Dc Voltage Rating In Volts:250.0 single mating end single contact groupingConnector Locking Method:Externally threaded shellThread Size:0.875 inches
Contact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:22.0 single mating end single contact groupingContact Maximum Ac Voltage Rating In Volts:200.0 single mating end single contact groupingContact Maximum Dc Voltage Rating In Volts:250.0 single mating end single contact groupingConnector Locking Method:Externally threaded shellThread Size:0.875 inchesInsert Material:
Contact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:22.0 single mating end single contact groupingContact Maximum Ac Voltage Rating In Volts:200.0 single mating end single contact groupingContact Maximum Dc Voltage Rating In Volts:250.0 single mating end single contact groupingConnector Locking Method:Externally threaded shellThread Size:0.875 inchesInsert Material:Plastic single mating end
Contact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:22.0 single mating end single contact groupingContact Maximum Ac Voltage Rating In Volts:200.0 single mating end single contact groupingContact Maximum Dc Voltage Rating In Volts:250.0 single mating end single contact groupingConnector Locking Method:Externally threaded shellInread Size:0.875 inchesInsert Material:Plastic single mating endShell Material:
Contact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:22.0 single mating end single contact groupingContact Maximum Ac Voltage Rating In Volts:200.0 single mating end single contact groupingContact Maximum Dc Voltage Rating In Volts:250.0 single mating end single contact groupingConnector Locking Method:Externally threaded shellInsert Material:Plastic single mating endShell Material:Aluminum alloy
Contact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:22.0 single mating end single contact groupingContact Maximum Ac Voltage Rating In Volts:200.0 single mating end single contact groupingContact Maximum Dc Voltage Rating In Volts:250.0 single mating end single contact groupingConnector Locking Method:Externally threaded shellThread Size:0.875 inchesInsert Material:Plastic single mating endShell Material:Aluminum alloy

Electrical Receptacle Connector - Page 2 of 2

AeroBase Group

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0