Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-883-8078

| Thread Class: |
|----------------------------------------------------------------------------------------|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape threaded |
| Overall Length: |
| 1.271 inches |
| Overall Diameter: |
| 1.500 inches |
| Environmental Protection: |
| Heat resistant and moisture resistant and salt water resistant and vibration resistant |
| Distance From Mounting Shoulder To Front Face: |
| 0.630 inches |
| Mounting Facility Thickness: |
| 0.125 inches |
| Threaded Device Type: |
| Mounting bushing |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 6-oct single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Bayonet pin |
| Thread Length: |
| 0.330 inches |
| Thread Size: |
| 1.125 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Silver single mating end single contact grouping |
| |



Insert Material: Plastic single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium **Included Contact Quantity:** 6 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round w/flat Included Contact Type: Round pin single mating end single contact grouping **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0