NSN 5935-00-883-9216

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-883-9216

View Online at https://aerobasegroup.com/nsn/5935-00-883-9216
Body Style:
Straight shape, internal coupling
Overall Length:
1.707 inches
Overall Diameter:
1.141 inches
Environmental Protection:
Moisture resistant
Cable Entrance Diameter:
0.375 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
19-2p single mating end
Contact Removability:
Removable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
7.5 single mating end 2nd contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings and silver single mating end all contact groupings
Insert Material:
Rubber single mating end
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy

NSN 5935-00-883-9216

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment: Cadmium and chromate Included Contact Quantity: 8 single mating end 2nd contact grouping Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location: Contact surfaces gold and contact surfaces silver Precious Material And Weight: 0.012 gold grains, troy and 0.012 silver grains, troy Precious Material: Gold and silver Shelf Life: N/a Unit Of Measure: ---

Demilitarization:

No Fiig: A039b0