Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-885-0348

Thread Class: 2a **Thread Direction: Right-hand Body Style:** Straight shape, external coupling **Overall Length:** 2.250 inches **Bushing Diameter:** 1.250 inches **Overall Height:** 2.000 inches **Overall Width:** 2.000 inches **Environmental Protection:** Weatherproof **Unthreaded Mounting Hole Diameter:** 0.257 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.438 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.438 inches **Threaded Device Type:** Coupling facility Mating End Quantity: 1 **Contact Position Arrangement Style:** Lc single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 52.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.250 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-00-885-0348

Electrical Receptacle Connector - Page 2 of 2



Copper a	lloy single mating end single contact grouping
	Surface Treatment:
Silver sin	gle mating end single contact grouping
Insert Ma	iterial:
Plastic po	lytetrafluoroethylene single mating end
Terminal	Туре:
Tab, solo	ler lug single mating end single contact grouping
Shell Ma	erial:
Copper a	lloy
Shell Su	face Treatment:
Silver	
Included	Contact Quantity:
1 single n	nating end single contact grouping
Included	Contact Type:
Coaxial s	ocket single mating end single contact grouping
Precious	Material And Location:
Contact a	nd shell surfaces silver
Precious	Material And Weight:
0.105 silv	er grains, troy
Precious	Material:
Silver	
Thread S	eries Designator:
Unef	
Shelf Life	<u>.</u>
N/a	
Unit Of N	leasure:
Demilitar	ization:
No	
Fiig:	
A039b0	