

View Online at <https://aerobasegroup.com/nsn/5935-00-888-9479>

Body Style:

Square flange mount

Bushing Diameter:

2.281 inches

Mounting Hole Circle Radius:

2.718 inches

Unthreaded Mounting Hole Diameter:

0.203 inches

Distance From Mounting Shoulder To Rear Face:

1.843 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

4 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

20.0 single mating end 2nd contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end 1st contact grouping

Polarization Method:

Contact

Shell Type:

Solid

Connector Locking Method:

Contact twistlock

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Insert Material:

Plastic phenolic single mating end

Terminal Type:

Screw single mating end all contact groupings

Shell Material:

Copper alloy

Shell Surface Treatment:

Nickel

Insert Material Specification:

Mil-m-14, ty cfg military specification single material response single mating end

Included Contact Quantity:

3 single mating end 2nd contact grouping

Included Contact Type:

Curved pin w/lock single mating end 2nd contact grouping

Special Features:

4 mtg holes

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.