NSN 5935-00-888-9603

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-888-9603

Body Style:

Straight shape, thru-hole mount, external coupling

Overall Length:

1.125 inches

Overall Diameter:

1.250 inches

Environmental Protection:

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

Distance From Mounting Shoulder To Front Face:

0.609 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

37p single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Potting

Connector Locking Method:

Spring friction

Connector Cable Strain Relief Method:

Potting type

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 type 1, class 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290

grade e federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium



Shell Surface Treatment Specification: Qq-p-416 type 2, class 3 federal specification single treatment response **Shell Material Specification:** Qq-a-591 federal specification single material response **Included Contact Quantity:** 37 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round **Included Contact Type:** Round pin single mating end single contact grouping **Special Features:** Solder flange mtg **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.037 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.