## NSN 5935-00-889-5105

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-889-5105

View Online at https://aerobasegroup.com/nsn/5935-00-889-5105
Body Style:
Straight shape, external coupling
Overall Length:
1.172 inches
Overall Height:
1.000 inches
Overall Width:
1.000 inches
Environmental Protection:
Corrosion resistant and humidity resistant and moisture resistant and oil resistant and shock proof and thermal shock resistant and vibration
resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.719 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.719 inches
Distance From Mounting Shoulder To Front Face:
0.531 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
1 row of contacts non-inserted board single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Detent
Terminal Location:
Back single mating end single contact grouping
Insert Material:
Rubber synthetic single mating end
Torminal Typo:

**Shell Material:** Aluminum alloy

Crimp single mating end single contact grouping

## NSN 5935-00-889-5105

Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response $\frac{1}{2}$
Included Contact Quantity:
7 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No