

View Online at <https://aerobasegroup.com/nsn/5935-00-889-5593>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape w/flange

Overall Length:

2.020 inches

Overall Height:

Between 1.969 inches and 2.031 inches

Overall Width:

Between 1.969 inches and 2.031 inches

Environmental Protection:

Pressure proof

Unthreaded Mounting Hole Diameter:

0.147 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.558 inches and 1.566 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.558 inches and 1.566 inches

Distance From Mounting Shoulder To Front Face:

Between 0.812 inches and 0.828 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

28-9 all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Current Rating In Amps:

41.0 all mating ends 2nd contact grouping

Contact Maximum Ac Voltage Rating In Volts:

900.0 all mating ends all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

1250.0 all mating ends all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Length:

0.625 inches

Thready Qty Per Inch (tpi):

18

Thread Size:

1.750 inches

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold and silver all mating ends all contact groupings

Insert Material:

Plastic all mating ends

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Included Contact Type:

Round socket 2nd mating end all contact groupings

Precious Material And Location:

Contact surface gold and contact surface silver

Precious Material:

Gold and silver

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0