
NSN 5935-00-889-7890

Tip Jack - Page 1 of 2

Thread Class:





2a **Thread Direction: Right-hand Electrical Insulation Feature:** Insulated from panel **Identification Code Color:** White **Body Style:** Threaded bushing mounted **Overall Length:** 0.922 inches Mounting Bushing Length: 0.563 inches **Body Length:** 0.797 inches **Overall Diameter:** 0.438 inches **Bushing Accommodation Hole Shape:** Round Maximum Voltage Rating In Volts: 750.0 ac Accommodated Finger Type: Banana spring single finger **Finger Accommodation Diameter:** 0.163 inches single finger Finger Accommodation Length: 0.563 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.313 inches Capacitance In Picofarads: 4.0 **Current Rating In Amps:** 15.0 Mounting Facility Type And Quantity: 1 bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.250 inches **Terminal Type:** Turret

NSN 5935-00-889-7890

Tip Jack - Page 2 of 2

Material:

Plastic insulator

Material:

Plastic insulator

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03400

