Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-889-8767

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, thru-hole mount, external coupling
Overall Length:
1.690 inches
Overall Diameter:
Between 1.796 inches and 1.828 inches
Distance From Mounting Shoulder To Front Face:
Between 0.868 inches and 0.900 inches
Mounting Facility Thickness:
Between 0.062 inches and 0.250 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
20-39 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end 2nd contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Connector Cable Strain Relief Method:
Potting type
Thready Qty Per Inch (tpi):
18
Thread Size:
1.375 inches

Electrical Receptacle Connector - Page 2 of 2



Back single	e mating end single contact grouping
Contact M	
	by single mating end single contact grouping
	urface Treatment:
	e mating end single contact grouping and silver single mating end single contact groupin
Insert Mat	
	gle mating end
Terminal T	
	s single mating end single contact grouping
Shell Mate	
Aluminum	alloy
Shell Surfa	ace Treatment:
Cadmium	
Included C	Contact Quantity:
37 single m	nating end 2nd contact grouping
Bushing A	accommodation Hole Shape:
Round w/fl	at
Included C	Contact Type:
Round pin	single mating end single contact grouping
Precious I	Material And Location:
Contact su	rface gold and contact surface silver
Precious I	Material:
Gold and s	ilver
Thread Se	ries Designator:
Unef	
Shelf Life:	
N/a	
Unit Of Me	easure:
Demilitariz	zation:
No	
Fiig:	