NSN 5935-00-890-9009

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-890-9009

Thread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape
Overall Length:
0.520 inches
Overall Height:
2.060 inches
Overall Width:
0.720 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.812 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.562 inches
Distance From Mounting Shoulder To Front Face:
0.320 inches
Threaded Device Type:
Coupling facility
Martin F. 10 and
Mating End Quantity:
1
1
1 Contact Position Arrangement Style:
1 Contact Position Arrangement Style: 75 single mating end
Contact Position Arrangement Style: 75 single mating end Contact Removability:
Contact Position Arrangement Style: 75 single mating end Contact Removability: Nonremovable single mating end single contact grouping
Contact Position Arrangement Style: 75 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps:
Contact Position Arrangement Style: 75 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping
Contact Position Arrangement Style: 75 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method:
Contact Position Arrangement Style: 75 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Jackscrew
Contact Position Arrangement Style: 75 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Jackscrew Connector Locking Method:
Contact Position Arrangement Style: 75 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Jackscrew Connector Locking Method: Screw lock pin
Contact Position Arrangement Style: 75 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Jackscrew Connector Locking Method: Screw lock pin Thread Size:
Contact Position Arrangement Style: 75 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Jackscrew Connector Locking Method: Screw lock pin Thread Size: 0.086 inches and 0.086 inches
Contact Position Arrangement Style: 75 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Jackscrew Connector Locking Method: Screw lock pin Thread Size: 0.086 inches and 0.086 inches Terminal Location:
Contact Position Arrangement Style: 75 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Jackscrew Connector Locking Method: Screw lock pin Thread Size: 0.086 inches and 0.086 inches Terminal Location: Back single mating end single contact grouping
Contact Position Arrangement Style: 75 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Jackscrew Connector Locking Method: Screw lock pin Thread Size: 0.086 inches and 0.086 inches Terminal Location: Back single mating end single contact grouping Insert Material:

Included Contact Quantity:

75 single mating end single contact grouping

NSN 5935-00-890-9009

Electrical Receptacle Connector - Page 2 of 2



Included	Contact	Ty	pe:
----------	---------	----	-----

Round socket single mating end single contact grouping

Thread Series Designator:

Unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0