## NSN 5935-00-890-9805

Solder well single mating end single contact grouping

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-890-9805 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 0.887 inches **Overall Diameter:** 1.500 inches **Distance From Mounting Shoulder To Front Face:** 0.696 inches **Mounting Facility Thickness:** 0.125 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 28-12 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet latch **Thread Size:** 1.125 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** 

## NSN 5935-00-890-9805

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
26 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surface gold and contact surface silver
Precious Material And Weight:
$0.026\ gold\ grains,\ troy\ and\ 0.026\ silver\ grains,\ troy$
Precious Material:
Gold and silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A039b0