NSN 5935-00-891-2720

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-891-2720

Body Style:
Single card
Overall Length:
4.279 inches
Overall Height:
0.458 inches
Overall Width:
0.343 inches
Environmental Protection:
Moisture resistant
Unthreaded Mounting Hole Diameter:
0.142 inches
Distance Between Mounting Facility Centers:
4.031 inches
Board Accommodated Width:
Between 0.054 inches and 0.070 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
Bridged contacts inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
600.0 single mating end single contact grouping
Polarization Method:
Contact to contact polarizing keys
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate mineral filled single mating end
Terminal Type:
Wire wrap single mating end single contact grouping
Included Contact Quantity:
22 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

NSN 5935-00-891-2720

Electrical Receptacle Connector - Page 2 of 2



Preciou	ıs Mate	erial Ar	nd Loc	cation:
---------	---------	----------	--------	---------

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.022 gold grains, troy and 0.022 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A039b0