Electrical Plug Connector - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-00-891-4956

| | d Quantity: |
|--------------|---|
| 1 | |
| Contact Re | emovability: |
| Nonremova | able single mating end single contact grouping |
| Contact Ma | aximum Current Rating In Amps: |
| 7.0 single n | nating end single contact grouping |
| Terminal L | ocation: |
| Back single | e mating end single contact grouping |
| Contact Ma | aterial: |
| Copper allo | by single mating end single contact grouping |
| Contact Su | urface Treatment: |
| Gold single | mating end single contact grouping |
| Contact Ma | aterial Specification: |
| Qq-b-330, d | comp a federal specification single material response single mating end single contact grouping |
| Included C | Contact Quantity: |
| 4 single ma | ating end single contact grouping |
| Included C | Contact Type: |
| Leaf spring | single mating end single contact grouping |
| Precious M | Naterial And Location: |
| Contact sur | rfaces gold |
| Precious M | Naterial And Weight: |
| 0.004 gold | grains, troy |
| Precious M | Naterial: |
| Gold | |
| Shelf Life: | |
| N/a | |
| Unit Of Me | basure: |
| | |
| Demilitariz | ration: |
| No | |
| Fiig: | |
| A039b0 | |