NSN 5935-00-891-8475

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-891-8475

Body Style:

Straight shape, internal coupling

Overall Length:

1.250 inches

Overall Diameter:

0.933 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant and shock resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

Ahag 7-50 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Push-pull

Operating Tempurature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Features Provided:

Color band engagement indicator

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade a military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

NSN 5935-00-891-8475

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment: Chromate and cadmium **Shell Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Shell Material Specification:** Qq-a-591 federal specification single material response **Insert Material Specification:** Mil-m-14 military specification single material response single mating end **Included Contact Quantity:** 7 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.007 gold grains, troy **Precious Material:** Gold **Test Data Document:** 81349-mil-c-81703 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 96906-ms3137 government standard Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.