NSN 5935-00-892-8662

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-892-8662

| Body Style: |
|---|
| Flush flange mounting |
| Overall Length: |
| 0.844 inches |
| Bushing Diameter: |
| 0.375 inches |
| Mounting Hole Circle Radius: |
| 0.593 inches |
| Overall Diameter: |
| 1.438 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.136 inches |
| Distance From Mounting Shoulder To Rear Face: |
| 0.750 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 5 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 7.5 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 133.0 single mating end single contact grouping |
| Polarization Method: |
| Contact |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Latch |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Silver single mating end single contact grouping |
| Insert Material: |
| Glass single mating end and plastic polyamide single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shall Material: |

Aluminum alloy

NSN 5935-00-892-8662

Electrical Receptacle Connector - Page 2 of 2

