## NSN 5935-00-892-8895

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-892-8895 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 1.156 inches **Overall Diameter:** 0.828 inches **Distance From Mounting Shoulder To Front Face:** 0.742 inches **Mounting Facility Thickness:** 0.156 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 13-12 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Contact Shell Type: **Connector Locking Method:** Shell twistlock **Thread Size:** 0.875 inches **Terminal Location:** Back single mating end single contact grouping **Insert Material:** Plastic single mating end

Terminal Type:

Solder well single mating end single contact grouping

## NSN 5935-00-892-8895

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
12 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fila

A039b0