## NSN 5935-00-892-8933

**Body Style:** 

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-892-8933

Straight shape, internal coupling w/strain relief
Body Length:
2.375 inches
Overall Diameter:
1.083 inches
Cable Entrance Diameter:
0.375 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
14-12 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
10.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Connector Cable Strain Relief Method:
Compression nut
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Contact Material Specification:

Qq-b-626 federal specification single material response single mating end single contact grouping

## NSN 5935-00-892-8933

Electrical Plug Connector - Page 2 of 2



## **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Insert Material Specification:** Mil-m-14, type mdg military specification single material response single mating end **Included Contact Quantity:** 12 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surface gold and contact surface silver **Precious Material And Weight:** 0.012 gold grains, troy and 0.012 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A039b0

Mil-m-14 spec.

Mil-std (military Standard):