NSN 5935-00-892-9054

Connector Adapter - Page 1 of 2

0.438 inches and 0.625 inches



View Online at https://aerobasegroup.com/nsn/5935-00-892-9054

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape w/flange
Overall Length:
1.375 inches
Overall Height:
1.000 inches
Overall Width:
1.000 inches
Environmental Protection:
Dust resistant and fungus resistant and salt water resistant and sand resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.713 inches and 0.723 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.713 inches and 0.723 inches
Distance From Mounting Shoulder To Front Face:
0.875 inches
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
2
Contact Position Arrangement Style:
N all mating ends
Contact Removability:
Nonremovable all mating ends single contact grouping
Contact Maximum Frequency Rating:
10000.0 megahertz all mating ends single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 all mating ends single contact grouping
Thready Qty Per Inch (tpi):
28 and 24
Thread Size:

NSN 5935-00-892-9054

Connector Adapter - Page 2 of 2

Fiig: A039b0



Contact Material:
Copper alloy all mating ends single contact grouping
Contact Surface Treatment:
Silver all mating ends single contact grouping
Insert Material:
Plastic tetrafluoroethylene all mating ends
Contact Material Specification:
Qq-c-530, comp ht federal specification single material response all mating ends single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Silver
Shell Material Specification:
Qq-b-626, comp 22 federal specification single material response
Included Contact Quantity:
1 all mating ends single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Coaxial socket all mating ends single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.010 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No