

View Online at <https://aerobasegroup.com/nsn/5935-00-892-9682>

Body Style:

Rectangular shape

Overall Length:

0.440 inches

Overall Height:

0.800 inches

Overall Width:

0.250 inches

Unthreaded Mounting Hole Diameter:

0.093 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

4 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

7.5 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

2000.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

2800.0 single mating end all contact groupings

Connector Locking Method:

Friction

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45402 military specification single treatment response single mating end all contact groupings

Terminal Type:

Solder well single mating end all contact groupings

Insert Material Specification:

Mil-m-14, ty sgd-f military specification single material response single mating end

Included Contact Quantity:

3 single mating end 2nd contact grouping

Included Contact Type:

Round socket single mating end 2nd contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.004 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45402 spec.