

View Online at <https://aerobasegroup.com/nsn/5935-00-893-8455>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Angle shape w/cable clamp

Overall Diameter:

1.588 inches

Body Angle In Deg:

135.0

Cable Entrance Diameter:

Between 0.445 inches and 0.750 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

22-19 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling nut

Connector Cable Strain Relief Method:

Cable clamp

Distance From Centerline To Connector End:

2.797 inches

Distance From Centerline To Cable End:

2.099 inches

Thread Size:

1.375 inches

Terminal Location:

Back single mating end single contact grouping

Insert Material:

Rubber single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Included Contact Quantity:

14 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Test Data Document:

03538-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 03538--53057 standard (includes industry or association standards, individual manufacturer standards, etc.). And 03538-re49d768 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0