## NSN 5935-00-894-3235

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-894-3235 **Thread Class:** 2a **Thread Direction:** Right-hand **Overall Length:** 1.500 inches **Overall Height:** 0.313 inches **Overall Width:** 0.313 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 353.0 single mating end single contact grouping **Shell Type:** Solid **Connector Locking Method:** Externally threaded coupling ring Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.313 inches **Insert Material:** Plastic tetrafluoroethylene single mating end **Shell Material:** Copper alloy **Shell Surface Treatment:** Silver **Shell Surface Treatment Specification:** Mil-f-14072 military specification single treatment response **Shell Material Specification:** Qq-b-626, comp 22 federal specification single material response **Included Contact Quantity:** 

1 single mating end single contact grouping **Bushing Accommodation Hole Shape:** 

Round

## NSN 5935-00-894-3235

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.005 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-f-14072 spec.