Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-894-3237

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Angle shape
Overall Length:
0.938 inches
Overall Height:
0.922 inches
Overall Width:
0.312 inches
Environmental Protection:
Corrosion resistant
Cable Entrance Diameter:
0.160 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
Smp single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Spring lock
Connector Cable Strain Relief Method:
Cable clamp
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thready Qty Per Inch (tpi):
32
Thread Size:
0.312 inches
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping

NSN 5935-00-894-3237

Electrical Receptacle Connector - Page 2 of 2



Plastic poly	rtetrafluoroethylene single mating end
	urface Treatment Specification:
	ederal specification single treatment response single mating end single contact grouping
Terminal T	
	single mating end single contact grouping
	aterial Specification:
	-
Shell Mate	composition 22 federal specification single material response single mating end single contact groupi
Copper allo	
	ace Treatment:
Silver	
	ace Treatment Specification:
	ederal specification single treatment response
-	rial Specification:
	composition 22 federal specification single material response
	Contact Quantity:
	ating end single contact grouping
	ccommodation Hole Shape:
Round	
	Contact Type:
	single mating end single contact grouping
-	Naterial And Location:
	d body surfaces silver
	A sear same server
	r grains, troy
Precious N	
Silver	
	ries Designator:
Unef	
Shelf Life:	
N/a	
Unit Of Me	asure:
Demilitariz	ration:
No	
Fiig:	
A039b0	