NSN 5935-00-894-8912

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-894-8912 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Angle shape w/cable clamp **Overall Diameter:** 1.461 inches **Body Angle In Deg:** 135.0 **Cable Entrance Diameter:** 1.250 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 20-29 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 80.0 Shell Type: **Connector Locking Method:** Internally threaded coupling nut **Connector Cable Strain Relief Method:** Cable clamp **Distance From Centerline To Connector End:** 6.672 inches **Thread Size:** 1.250 inches **Terminal Location:**

Back single mating end single contact grouping

NSN 5935-00-894-8912Electrical Plug Connector - Page 2 of 2



Insert Material:
Rubber single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
17 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
VU30PU