## NSN 5935-00-897-0101

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-897-0101 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape Center To Center Distance Between Mounting Facilities Parallel To Length: Between 3.871 inches and 3.879 inches **Overall Height:** 1.250 inches **Overall Width:** Between 1.146 inches and 1.166 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.071 inches and 1.081 inches **Threaded Device Type:** Mounting stud **Mating End Quantity: Contact Position Arrangement Style:** 98 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1700.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid Thready Qty Per Inch (tpi): **Thread Size:** 0.138 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic phenolic single mating end

## NSN 5935-00-897-0101

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Pin single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Shell Material Specification:
Qq-a-591, comp 10 federal specification single material response
Insert Material Specification:
Mil-m-14, ty mdg military specification single material response single mating end
Included Contact Quantity:
98 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.098 gold grains, troy and 0.098 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.