NSN 5935-00-897-2156

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-897-2156

Body Style:
Straight shape
Overall Length:
3.344 inches
Overall Height:
0.750 inches
Overall Width:
0.469 inches
Unthreaded Mounting Hole Diameter:
0.156 inches
Distance Between Mounting Facility Centers:
3.000 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
2500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
3500.0 single mating end single contact grouping
Polarization Method:
Contact
Shell Type:
Solid
Connector Locking Method:
Jackscrew-socket
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy

NSN 5935-00-897-2156

Mil-m-14 spec.

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Insert Material Specification:
Mil-m-14, type mdg military specification single material response single mating end
Included Contact Quantity:
15 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.015 gold grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):