## NSN 5935-00-898-0913

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-898-0913

Body Style:		
Straight shape		
Overall Length:		
3.971 inches		
Overall Height:		
0.750 inches		
Overall Width:		
0.671 inches		
Unthreaded Mounting Hole Diameter:		
Between 0.151 inches and 0.161 inches		
Distance Between Mounting Facility Centers:		
Between 3.615 inches and 3.635 inches		
Mating End Quantity:		
1		
Contact Position Arrangement Style:		
1 row of contacts non-inserted board single mating end		
Contact Removability:		
Nonremovable single mating end single contact grouping		
Contact Maximum Current Rating In Amps:		
7.5 single mating end single contact grouping		
Polarization Method:		
Mating end		
Shell Type:		
Solid		
Terminal Location:		
Side single mating end single contact grouping		
Contact Material:		
Copper alloy single mating end single contact grouping		
Contact Surface Treatment:		
Gold single mating end single contact grouping and silver single mating end single contact grouping		
Insert Material:		
Plastic diallyl phthalate single mating end		
Terminal Type:		
Pin single mating end single contact grouping		
Shell Material:		
Aluminum alloy		
Shell Surface Treatment:		
Cadmium		
Insert Material Specification:		
Mil-m-19833, type gdi-30f military specification single material response single mating end		

Included Contact Quantity:

19 single mating end single contact grouping

## NSN 5935-00-898-0913

Electrical Receptacle Connector - Page 2 of 2



Included	Contact	Type:
----------	---------	-------

Round pin single mating end single contact grouping

**Special Features:** 

Right-angle, pcb mtg. Type, accomodates 1/8in. Pcb

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:** 

0.028 gold grains, troy and 0.028 silver grains, troy

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.