## NSN 5935-00-899-7901

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-899-7901 **Thread Class:** 2a and 2b and 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 0.870 inches **Overall Height:** 0.500 inches **Overall Width:** 0.380 inches **Distance Between Mounting Facility Centers:** 0.656 inches **Threaded Device Type:** Coupling facility and mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** "18, 18-20" single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Polarization Method:** Jackscrew Shell Type: Solid **Connector Locking Method:** Jackscrew-socket Thready Qty Per Inch (tpi): **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

## NSN 5935-00-899-7901

Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Included Contact Quantity:
18 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Jackscrew type-female and location-left handandjackscrew type-male and location-right hand
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.018 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No