

View Online at <https://aerobasegroup.com/nsn/5935-00-900-1985>

Body Style:

Straight shape, external coupling w/strain relief

Overall Length:

1.870 inches

Diameter:

0.817 inches

Overall Diameter:

0.895 inches

Environmental Protection:

Vibration resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

22251 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

12.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet shell

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Shell Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Insert Material Specification:

Mil-m-14 military specification single material response single mating end

Included Contact Quantity:

3 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.