## NSN 5935-00-900-3463

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-900-3463

**Body Style:** Straight shape, internal coupling Overall Length: 1.203 inches **Overall Diameter:** 1.484 inches **Environmental Protection:** Pressure proof and heat resistant and moisture resistant and vibration resistant and watertight **Mating End Quantity: Contact Position Arrangement Style:** 36-21 single mating end **Contact Removability:** Removable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 7.5 single mating end 1st contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Potting **Connector Locking Method:** Ball **Connector Cable Strain Relief Method:** Potting type Radio Frequency Type Contact Characteristic Impedance In Ohms: 95.0 single mating end 2nd contact grouping **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings and silver single mating end all contact groupings **Insert Material:** Plastic silicone single mating end **Terminal Type:** Crimp single mating end all contact groupings **Shell Material:** Aluminum alloy **Shell Surface Treatment:** 

Cadmium

## NSN 5935-00-900-3463

Electrical Plug Connector - Page 2 of 2



## **Included Contact Quantity:**

30 single mating end 1st contact grouping

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:** 

0.035 gold grains, troy and 0.035 silver grains, troy

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0