

View Online at <https://aerobasegroup.com/nsn/5935-00-900-3497>

Body Style:

Straight shape

Overall Length:

Between 2.620 inches and 2.650 inches

Overall Height:

0.645 inches

Overall Width:

Between 0.590 inches and 0.620 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.086 inches

Distance Between Mounting Facility Centers:

Between 2.401 inches and 2.411 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

50 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Contact

Shell Type:

Solid

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Astem b139, alloy b2 assn standard single material response single mating end single contact grouping

Shell Material:

Steel comp 1017

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Shell Material Specification:

Qq-s-636 federal specification single material response

Insert Material Specification:

Mil-m-19833, type gdi-30f military specification single material response single mating end

Included Contact Quantity:

50 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.050 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.