NSN 5935-00-900-3931

Straight shape, flange mount, external coupling

Contact Surface Treatment Specification:

e federal specification 2nd treatment response single mating end single contact grouping

Body Style:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-900-3931

Overall Length:
1.963 inches
Overall Height:
1.578 inches
Overall Width:
1.578 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.250 inches
Distance From Mounting Shoulder To Front Face:
Between 0.556 inches and 0.587 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
22-21 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1000.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Potting
Connector Locking Method:
Bayonet pin
Connector Cable Strain Relief Method:
Potting type
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping

Mil-g-45204 type 1, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290 grade

NSN 5935-00-900-3931

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 type 2, cl 3 federal specification single treatment response
Shell Material Specification:
Qq-a-591 federal specification single material response
Included Contact Quantity:
21 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.021 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms3120 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.