## NSN 5935-00-900-8837

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-900-8837 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight type **Overall Length:** 3.719 inches **Overall Height:** 0.672 inches **Overall Width:** Between 0.338 inches and 0.348 inches **Distance Between Mounting Facility Centers:** 3.406 inches **Threaded Device Type:** Mounting hole **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 2 rows of independent contacts inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Tab, solder lug single mating end single contact grouping **Insert Material Specification:** 

Mil-m-14f, ty sdgf military specification single material response single mating end

**Included Contact Quantity:** 

36 single mating end single contact grouping

## NSN 5935-00-900-8837

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Leaf spring single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.036 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-m-14f spec.