NSN 5935-00-900-9126

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-900-9126

Body Style: Straight shape **Overall Length:** Between 2.620 inches and 2.650 inches **Overall Height:** 0.683 inches **Overall Width:** Between 0.590 inches and 0.620 inches **Environmental Protection:** Moisture resistant **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches **Distance Between Mounting Facility Centers:** Between 2.401 inches and 2.411 inches **Mating End Quantity: Contact Position Arrangement Style:** 50 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Steel **Shell Surface Treatment:** Cadmium and chromate

Insert Material Specification:

Mil-m-19833, type gdi-30f military specification single material response single mating end

NSN 5935-00-900-9126

Electrical Receptacle Connector - Page 2 of 2



ncluded	Contact	Quantity:
---------	---------	-----------

50 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.050 gold grains, troy and 0.050 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.